



# TIKEN BEARINGS CO.,LTD.



24130 CCK30/C3W33 Bearing 2D drawings and 3D CAD models

5.906 Inch | 150 Millimeter x 9.843 Inch | 250 Millimeter x 3.937 Inch | 100 Millimeter SKF 24130 CCK30/C3W33 Spherical Roller Bearings

Bearing No. 24130 CCK30/C3W33

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	19.448
EAN	7316577004840
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH24130 (Specify bore)
Withdrawal Nut	KM30
Inch - Metric	Metric
Long Description	150MM Tapered Bore; 250MM Outside Diameter; 100MM Width; C3-Loose Clearance; Adapter Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable
Other Features	Order adapter or



## TIKEN BEARINGS CO.,LTD.

	withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Weight / LBS	42.836
D	9.843 Inch   250 Millimeter
d	5.906 Inch   150 Millimeter
B	3.937 Inch   100 Millimeter
bore diameter:	150 mm
maximum rpm:	2000 RPM
outside diameter:	250 mm
operating temperature range:	Maximum of +390 ° F
overall width:	110 mm
cage material:	Steel
bore type:	Tapered 1:30
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	100 mm
dynamic load capacity:	1020 kN
fillet radius:	2 mm
static load capacity:	1530 kN



# TIKEN BEARINGS CO.,LTD.

series:

241