



# TIKEN BEARINGS CO.,LTD.



24140 CCK30/C3W33 Bearing 2D drawings and 3D CAD models

7.874 Inch | 200 Millimeter x 13.386 Inch | 340 Millimeter x 5.512 Inch | 140 Millimeter SKF 24140 CCK30/C3W33 Spherical Roller Bearings

Bearing No. 24140 CCK30/C3W33

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	54.55
EAN	7316577005038
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH24140 (Specify bore)
Withdrawal Nut	HM42T
Inch - Metric	Metric
Long Description	200MM Tapered Bore; 340MM Outside Diameter; 140MM Width; C3-Loose Clearance; Adapter Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable
Other Features	Order adapter or



## TIKEN BEARINGS CO.,LTD.

	withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Weight / LBS	120.152
B	5.512 Inch   140 Millimeter
D	13.386 Inch   340 Millimeter
d	7.874 Inch   200 Millimeter
bore diameter:	200 mm
maximum rpm:	1400 RPM
outside diameter:	340 mm
operating temperature range:	Maximum of +390 ° F
overall width:	140 mm
cage material:	Steel
bore type:	Tapered 1:30
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	140 mm
dynamic load capacity:	1800 kN
fillet radius:	2.5 mm
static load capacity:	2800 kN



# TIKEN BEARINGS CO.,LTD.

series:	241
---------	-----